


MC110











Printing ID cards
has never been
so easy



Matica's MC110 has been designed to simplify card issuance, thanks to its user friendly, **'plug & print'** operation.

The MC110 is the ideal solution for establishing an in-house ID card issuance program and is widely used by membership organisations and small to medium sized businesses. Based on Matica's robust and reliable print engine, the MC110 prints vibrant, colorful cards every time.


Upgradable from single to dual-sided, the MC110 is also available with a contact/contactless encoder for the issuance of smart cards for access and entry control.

Print type  Dye sublimation	300 dpi  Resolution	Print mode  1 or 2 sided	150 cph  Full color	700 cph  Monochrome
Easy to use  Plug & print	Input capacity  100	Output capacity  30	Warranty  2 years	Encoding options 



MC110 delivers...

- ▶ High quality 300dpi printing
- ▶ Up to 150 color cards per hour
- ▶ Single to dual-sided upgrade
- ▶ Robust, reliable build quality
- ▶ Smart card encoding option
- ▶ 2 years warranty



Ideal for...

- ▶ Mid to low volume card issuance

MC110

Printer specifications

Print technology

Dye-sublimation, direct-to-card

Print resolution

300 dpi

Print area

53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

Print speed

- 150 cph (YMCKO single-side)
- 700 cph (monochrome printing)

Print mode

Single-sided / optional dual-sided

Printer memory

128 Mb

Communications interface

USB 2.0

Easy to use, plug and print operation

- 4 x LED status indicators
- Full front operation
- Drop in ribbon cassette with easy handling
- Automatic ribbon identification and setting
- Easy reach power button
- Easy maintenance access

Printer security

Support for Kensington® security lock

Printer dimensions (HxWxD)

256 x 202 x 405 mm / 10.6" x 7.9" x 15.9"

Weight

10 kg, 22 lb

Power supply

- 220-240V/110-115V, 50-60 Hz
- Standby mode and reduced power consumption

Operating environment

- Temperature: 15°C - 40°C, 59°F - 104°F
- Humidity: 20% - 65% (non-condensing)

Storage conditions

- Temperature: -5°C to 70°C, 23°F to 158°F
- Humidity: 20% to 70% (non-condensing)

Sound (ISO 7779)

Sound pressure less than 48dB (A)

Certifications

RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA)

Warranty

2 years (subject to the use of chromXpert® ribbons)

Card specifications

Input hopper capacity

100 cards (0.76 mm / 30 mil thickness)

Output hopper capacity

30 cards (front)

Card thickness

- 0.25 mm - 1.25 mm / 10 mil - 50 mil
- Gauge adjustment

Card types

CR-80 PVC, PVC-C

Software specifications

XPS printer driver

Windows® (32/64bit) 7, 8.1, 10, 11, Server 2012, 2016, 2019, 2022

Options

Smart card / contactless encoding

- Contact PC/SC, EMV compliant
- Smart contact station: ISO 7816-2
- ISO14443A, B, ISO15693, MIFARE®, DESFire®, HID iClass®


Dual-side activation kit

PR10300016



chromXpert Consumables

- To ensure print quality and card durability, printhead lifespan and overall printer reliability, use chromXpert ribbons only.
- Supply cores and cassettes are recyclable. Packaging is recycled.



ChromXpert™ ribbon program	Part No.
• YMCKO (250 prints)	PR20319301
• YMCKO-K (200 prints)	PR20319302
• ymc-KO (400 prints, half panel)	PR20319303
• KO (600 prints)	PR20305304
• Monochrome K (up to 2000 prints)	PR20314305
Cleaning kit	PR20309610



Global offices

Europe: Switzerland HQ, Italy, UK and Germany

Asia: Malaysia, China and India

USA: Minneapolis HQ, South Carolina and San Francisco

Middle East: Dubai



MC110 Datasheet A4 UK V2

Data subject to change without notice. All trademarks stated are the property of their respective owners.

Authorized reseller / System integrator



Toll-Free USA/Canada:
+1 800-943-2341

US: <https://www.aptika.com/>
Canada: <https://www.aptika.ca/>