

Sigma DS1 Direct-to-Card Printer

HIGHLIGHTS

Sigma: The next generation of direct-to-card printing

Entrust Sigma ID Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue secure identities.

- Simple: From unboxing to issuing ID cards and mobile flashpasses to managing your printer, we made sure Sigma was the most user-friendly ID card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will help protect your cards and your customers' data during each step of the issuance process
- Smart: Forward-thinking technology and scalability allow you to expand your ID card program as your needs evolve

KEY FEATURES & BENEFITS

The world's most user-friendly ID card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help - all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Optional pre-loaded ribbon cassettes make switching ribbons easy
- Innovative patented printhead protector feature shields the printhead during ribbon replacement or printer servicing, which helps to extend the printhead life. Enables you to easily fix the issue at hand without having to worry about damaging the printhead.



Sigma DS1 Direct-to-Card Printer

Unmatched security

- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Luster printing and other security features added to cards protect from tampering and counterfeiting

Flexibility and scalability built for the future

- Issuance capabilities include physical cards and digital mobile flashpass
- Choose on-premises or cloud-hosted deployment
- Expand your ID program as your needs change by adding smart card capabilities, WiFi connectivity, and more
- Print anytime, anywhere with your mobile device (iOS, Android, Windows)





Sigma DS1 Direct-to-Card Printer

TECHNICAL SPECIFICATIONS

Standard Features & Supplies

Dye-sublimation/resin thermal transfer		
Single-sided, rewritable technology		
300 dots per inch (dpi) (300 X 600, 300 X 1200)		
Single-sided color ribbon: Up to 175 cards per hour (cph) Monochrome printing: Up to 660 cards per hour (cph), single-sided		
Input hopper - 125 cards Output hopper - 25 cards		
Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79, CR-80		
Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH – non condensing		
L 17.4 in x W 8.9 in x H 9 in / 44.2 cm x 22.6 cm x 22.9 cm		
11.3 lbs (5.49 kg)		
USB		
36 months		
Windows 10 versions, 32- and 64-bit Windows 8.1, 32- or 64-bit Windows Server 2019 Windows Server 2016 Windows Server 2012, R2, 64-bit		





Sigma DS1 Direct-to-Card Printer

Optional Features & Supplies

Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option		
WiFi	WiFi types: 802.11g/n Authentication modes: None, WPA2 Personal Dual-band 2.4GHz & 5GHz		
Loosely coupled:	ISO 14443 A/B, ISO 15693, MIFARE, MIFARE DESFire EV1/EV2, HID Prox, iClass, iClass SE, iClass Seos		
Color ribbons*	Prefilled ribbon cassettes:		
	YMCKT	500 images	
	KTT	750 images	
	Refill ribbon kits:		
	YMCKT	250/500 images	
	ymcKT	650 images	
	KT	1,000 images	
	KTT	750 images	
	YMCKF-KT	300 images	
	YMCKL-KT	300 images	
Monochrome ribbons	Refill print ribbon kits in black, white, blue, red, green, scratch-off, silver matte, gold matte, silver metallic, and gold metallic: 1,500 images		

^{*} Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, F=UV fluorescent, L=Luster, y=1/2 panel Yellow, m=1/2 panel Magenta, c=1/2 panel Cyan, S=Silver matte, G=Gold matte.

Panel print ribbon yields stated are typically the maximum number of panel sets per roll.

Monochrome print ribbon yields stated are the minimum achievable per roll. Actual yields may be more than 3 times greater due to Entrust monochrome ribbon saver features.

* Also available as manual feed configuration. Please refer to Sigma DS1 Direct-to-Card Printer Manual Feed Data Sheet for more information.









